

VOLTAGE CONTROLLED OSCILLATOR

TOM9306
250 - 500 MHz

Available as:

TOM9306, 4 Pin TO-8 (T4)
TON9306, 4 Pin Surface Mount (SM3)
TOP9306, 4 Pin Flatpack (FP4)
BXO9306, Connectorized Housing (H1)

Features

- Low Noise Bipolar Transistor
- Broad Tuning Range
- Operating Case Temp. -55 °C to + 85 °C
- Environmental Screening available

Specifications



CHARACTERISTIC	TYPICAL Ta = 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	250 - 500 MHz	250 - 500 MHz
Output Power (dBm)	+12	+10.0 Min.
Power Flatness (dB)	± 0.4	± 1.0 Max.
Tuning Voltage Range (v)	1 to 18	0 to 20
Tuning Voltage Sensitivity (MHz/V)	15	5 Min.
Harmonics (dBc)	-17	-10 Max.
Spurious (dBc)	<-80	- 80 Max.
3dB Modulation BW, Zg = 50 Ohms	--	4MHz Min.
Pushing (MHz/V)	1	3.0 Max.
Pulling (MHz); 12 dB RL	3	8.0 Max.
Frequency Drift (MHz/°C)	--	0.05 Max.
Power Vdc	+15	+15
mA	15	20.0

Maximum Ratings


Ambient Operating Temperature -55°C to + 100 °C
Storage Temperature -62°C to + 125 °C
Case Temperature + 125 °C
DC Voltage + 20 Volts
Maximum DC Tuning Voltage + 20 Volts
Minimum DC Tuning Voltage 0 Volts

Note: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data



Legend ——— + 25 °C - - - +85 °C ······ -55 °C



Notes:

1. Phase Noise is measured using the Aeroflex PN9000.
2. Worst case phase noise @ 100KHz offset across frequency range and temperature extremes is -120dBc/Hz.

AMPLIFONIX

2707 Black Lake Place, Philadelphia, PA 19154

TEL 215-464-4000 •••• FAX 215-464-4001

04/11/02