

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI MRF427** is Designed for high voltage applications up to 30 MHz

FEATURES:

- $P_G = 18$ dB min. at 25 W/30 MHz
- $IMD_3 = -34$ dBc max. at 25 W_(PEP)
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	6.0 A
V_{CBO}	110 V
V_{CEO}	65 V
V_{EBO}	4.0 V
P_{DISS}	80 W @ $T_C = 25^\circ C$
T_J	$-65^\circ C$ to $+200^\circ C$
T_{STG}	$-65^\circ C$ to $+150^\circ C$
θ_{JC}	2.19 $^\circ C/W$

PACKAGE STYLE .500 4L FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.125 / 3.18	
C	.245 / 6.22	.255 / 6.48
D	.720 / 18.28	.730 / 18.54
E	.125 / 3.18	
F	.970 / 24.64	.980 / 24.89
G	.495 / 12.57	.505 / 12.83
H	.003 / 0.08	.007 / 0.18
I	.090 / 2.29	.110 / 2.79
J	.150 / 3.81	.175 / 4.45
K		.280 / 7.11
L	.980 / 24.89	1.050 / 26.67

ORDER CODE: ASI10467

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 100$ mA	110			V
BV_{CES}	$I_C = 100$ mA	110			V
BV_{CEO}	$I_C = 200$ mA	65			V
BV_{EBO}	$I_E = 10$ mA	4.0			V
h_{FE}	$V_{CE} = 5.0$ V $I_C = 500$ mA	15		90	---
C_{ob}	$V_{CB} = 50$ V $f = 1.0$ MHz			60	pF
G_P IMD_3	$V_{CE} = 50$ V $P_{OUT} = 25$ W (PEP) $f = 30$ MHz	18	20 - 37	-34	dB dBc