


LM2901, LM339/LM339A, LM3302 LM239/LM239A Quad Comparator

Features


- Single or Dual Supply Operation
- Wide Range of Supply Voltage
LM2901, LM339/LM339A, LM239/LM239A: 2 ~ 36V
(or $\pm 1 \sim \pm 18V$)
LM3302: 2 ~ 28V (or $\pm 1 \sim \pm 14V$)
- Low Supply Current Drain 800 μA Typ.
- Open Collector Outputs for Wired and Connectors
- Low Input Bias Current 25nA Typ.
- Low Input Offset Current $\pm 2.3nA$ Typ.
- Low Input Offset Voltage $\pm 1.4mV$ Typ.
- Input Common Mode Voltage Range Includes Ground.
- Low Output Saturation Voltage
- Output Compatible With TTL, DTL and MOS Logic System

Description


The LM2901, LM339/LM339A, LM239/LM239A, LM3302 consist of four independent voltage comparators designed to operate from single power supply over a wide voltage range.



Internal Block Diagram



Schematic Diagram



Absolute Maximum Ratings

| Parameter | Symbol | Value | Unit |
|--|-------------|-----------------------------------|-------------|
| Supply Voltage | V_{CC} | ± 18 or 36 | V |
| Supply Voltage only LM3302 | V_{CC} | ± 14 or 28 | V |
| Differential Input Voltage | $V_I(DIFF)$ | 36 | V |
| Differential Input Voltage Only LM3302 | $V_I(DIFF)$ | 28 | V |
| Input Voltage | V_I | -0.3 to +36 | V |
| Input Voltage Only LM3302 | V_I | -0.3 to +28 | V |
| Output Short Circuit to GND | - | Continuous | - |
| Power Dissipation | P_D | 570 | mW |
| Operating Temperature LM339/LM339A LM2901/LM3302 LM239/LM239A | T_{OPR} | 0 ~ +70 -40 ~ +85 -25 ~ +85 | $^{\circ}C$ |
| Storage Temperature | T_{STG} | -65 ~ +150 | $^{\circ}C$ |

Electrical Characteristics

(VCC = 5V, TA = 25°C, unless otherwise specified)

| Parameter | Symbol | Conditions | LM239A/LM339A | | | LM239/LM339 | | | Unit |
|---------------------------------|----------------------|--|-------------------------|------|----------------------|-------------|------|----------------------|------|
| | | | Min. | Typ. | Max. | Min. | Typ. | Max. | |
| Input Offset Voltage | V _{IO} | V _{O(P)} = 1.4V, R _S = 0Ω | - | 1 | 2 | - | 1.4 | 5 | mV |
| | | Note1 | - | - | 4.0 | - | - | 9.0 | |
| Input Offset Current | I _{IO} | I _{IN(+)} - I _{IN(-)} , V _{CM} = 0V | - | 2.3 | 50 | - | 2.3 | 50 | nA |
| | | Note1 | - | - | 150 | - | - | 150 | |
| Input Bias Current | I _{BIAS} | V _{CM} = 0V | - | 57 | 250 | - | 57 | 250 | nA |
| | | Note1 | - | - | 400 | - | - | 400 | |
| Input Common Mode Voltage Range | V _{I(R)} | V _{CC} = 30V | 0 | - | V _{CC} -1.5 | 0 | - | V _{CC} -1.5 | V |
| | | Note1 | 0 | - | V _{CC} -2 | 0 | - | V _{CC} -2 | |
| Supply Current | I _{CC} | V _{CC} = 5V, R _L = ∞ | - | 1.1 | 2.0 | - | 1.1 | 2.0 | mA |
| Voltage Gain | G _V | V _{CC} = 15V, R _L ≥ 15kΩ (for large swing) | 50 | 200 | - | 50 | 200 | - | V/mV |
| Large Signal Response Time | T _{LRES} | V _I = TTL Logic Swing V _{REF} = 1.4V, V _{RL} = 5V, R _L = 5.1kΩ (Note2) | - | 300 | - | - | 300 | - | ns |
| Response Time | T _{RES} | V _{RL} = 5V, R _L = 5.1kΩ (Note2) | - | 1.3 | - | - | 1.3 | - | μs |
| Output Sink Current | I _{SINK} | V _{I(-)} ≥ 1V, V _{I(+)} = 0V, V _{O(P)} ≤ 1.5V | 6 | 18 | - | 6 | 18 | - | mA |
| Output Saturation Voltage | V _{SAT} | V _{I(-)} ≥ 1V, V _{I(+)} = 0V | - | 140 | 400 | - | 140 | 400 | mV |
| | | I _{SINK} = 4mA | Note1 | - | - | 700 | - | - | |
| Output Leakage Current | I _{o(LKG)} | V _{I(-)} = 0V | V _{O(P)} = 5V | - | 0.1 | - | - | 0.1 | nA |
| | | V _{I(+)} = 1V | V _{O(P)} = 30V | - | - | 1.0 | - | - | 1.0 |
| Differential Voltage | V _{I(DIFF)} | Note1 | - | - | 36 | - | - | 36 | V |

Note:

- LM339/LM339A : 0 ≤ T_A ≤ +70°C
LM2901/LM3302 : -40 ≤ T_A ≤ +85°C
LM239/LM239A : -25 ≤ T_A ≤ +85°C
- These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (Continued)

(VCC = 5V, TA = 25°C, unless otherwise specified)

| Parameter | Symbol | Conditions | LM2901 | | | LM3302 | | | Unit |
|---------------------------------|----------------------|--|--------|------|-------------|--------|------|-------------|----------|
| | | | Min. | Typ. | Max. | Min. | Typ. | Max. | |
| Input Offset Voltage | V _{IO} | VO(P) = 1.4V, RS = 0Ω | - | 2 | 7 | - | 2 | 20 | mV |
| | | Note1 | - | 9 | 15 | - | - | 40 | |
| Input Offset Current | I _{IO} | | - | 2.3 | 50 | - | 3 | 100 | nA |
| | | Note1 | - | 50 | 200 | - | - | 300 | |
| Input Bias Current | I _{BIAS} | | - | 57 | 250 | - | 57 | 250 | nA |
| | | Note1 | - | 200 | 500 | - | - | 1000 | |
| Input Common Mode Voltage Range | V _{I(R)} | LM2901, VCC = 30V LM3302, VCC = 28V | 0 | - | VCC -1.5 | 0 | - | VCC -1.5 | V |
| | | Note1 | 0 | - | VCC -2 | 0 | - | VCC -2 | |
| Supply Current | I _{CC} | RL = ∞, VCC = 5V | - | 1.1 | 2.0 | - | 1.1 | 2.0 | mA |
| | | RL = ∞, VCC = 30V (LM3302, VCC = 28V) | - | 1.6 | 2.5 | - | 1.6 | 2.5 | |
| Voltage Gain | G _V | VCC = 15V, RL ≥ 15kΩ (for large swing) | 25 | 100 | - | 2 | 30 | - | V/ mV |
| Large Signal Response Time | T _{LR} | V _I = TTL Logic Swing VREF = 1.4V, VRL = 5V, RL = 5.1kΩ (Note2) | - | 300 | - | - | 300 | - | ns |
| Response Time | T _{RES} | VRL = 5V, RL = 5.1kΩ (Note2) | - | 1.3 | - | - | 1.3 | - | μs |
| Output Sink Current | I _{SINK} | V _{I(-)} ≥ 1V, V _{I(+)} = 0V, V _{O(P)} ≤ 1.5V | 6 | 18 | - | 6 | 18 | - | mA |
| Output Saturation Voltage | V _{SAT} | V _{I(-)} ≥ 1V, V _{I(+)} = 0V | - | 140 | 400 | - | 140 | 400 | mV |
| | | I _{SINK} = 4mA | - | - | 700 | - | - | 700 | |
| Output Leakage Current | I _{O(LKG)} | V _{I(-)} = 0V | - | 0.1 | - | - | 0.1 | - | nA |
| | | V _{I(+)} = 1V | - | - | 1.0 | - | - | 1.0 | μA |
| Differential Voltage | V _{I(DIFF)} | Note1 | - | - | 36 | - | - | 28 | V |

Note:

- LM339/LM339A : 0 ≤ TA ≤ +70°C
LM2901/LM3302 : -40 ≤ TA ≤ +85°C
LM239/LM239A : -25 ≤ TA ≤ +85°C
- These parameters, although guaranteed, are not 100% tested in production.

Typical Performance Characteristics




Figure 1. Supply Current vs Supply Voltage




Figure 2. Input Current vs Supply Voltage




Figure 3. Output Saturation Voltage vs Sink Current




Figure 4. Response Time for Various Input Overdrive-Negative Transition





Figure 5. Response Time for Various Input Overdrive-Positive Transition

Mechanical Dimensions

Package

Dimensions in millimeters

14-DIP




Mechanical Dimensions (Continued)

Package

Dimensions in millimeters

14-SOP



Ordering Information

| Product Number | Package | Operating Temperature |
|----------------|---------|-----------------------|
| LM339N | 14-DIP | 0 ~ +70°C |
| LM339AN | | |
| LM339M | 14-SOP | |
| LM339AM | | |
| LM2901N | 14-DIP | -40 ~ +85°C |
| LM2901M | 14-SOP | |
| LM3302N | 14-DIP | |
| LM3302M | 14-SOP | |
| LM239N | 14-DIP | -25 ~ +85°C |
| LM239AN | | |
| LM239M | 14-SOP | |
| LM239AM | | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.