

23A003

0.3 Watts, 15 Volts, Class A
Linear to 2300 MHz

GENERAL DESCRIPTION

The 23A003 is a COMMON EMITTER transistor capable of providing 0.3 Watts of Class A, RF output power to 2300 MHz. This transistor is specifically designed for general Class A amplifier applications. It utilizes gold metalization and diffused ballasting to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder Sealed package.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C 3.0 Watts


Maximum Voltage and Current

BVces	Collector to Emitter Voltage	50 Volts
BVebo	Emitter to Base Voltage	3.5 Volts
Ic	Collector Current	0.3 Amps

Maximum Temperatures

Storage Temperature	- 65 to + 200°C
Operating Junction Temperature	+ 200°C

CASE OUTLINE 55BT, STYLE 2 B08



ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Out	F = 2.3 GHz	0.3			Watts
Pin	Power Input	Ic = 100 mA			0.03	Watts
Pg	Power Gain	Vcc = 15 Volts	10.0	11.0		dB
Ft	Transition Frequency	Vce = 15V, Ic = 100 mA	4.2	4.5		GHz
VSWR	Load Mismatch Tolerance				10:1	

BVebo	Emitter to Base Breakdown	Ie = 2 mA	3.5			Volts
BVces	Collector to Emitter Breakdown	Ic = 20 mA	50			Volts
BVceo	Collector to Emitter Breakdown	Ic = 20 mA	20			Volts
hFE	DC Current Gain	Vce = 5 V, Ic = 100 mA	20			
Cob	Capacitance	Vcb = 20V, f = 1 MHz		2.5		pF
θjc	Thermal Resistance				45	°C/W

Initial Issue November 1996

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

GHz Technology Inc. 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120