



| Characteristics   | Typical | Guaranteed |               |
|---|---------|------------|---------------|
|   |         | +25°C      | -54° to +85°C |
| SSB Conversion Loss & SSB Noise Figure (max.)<br>$f_{R=}$ $f_{L=}$ $f_{I=}$<br>$f_{R=}$ $f_{L=}$ $f_{I=}$<br>$f_{R=}$ $f_{L=}$ $f_{I=}$<br>$f_{R=}$ $f_{L=}$ $f_{I=}$ |         |            |               |
| Isolation (min.)<br>L to R<br>$f_{L=}$<br>$f_{L=}$<br>$f_{L=}$<br>L to I<br>$f_{L=}$<br>$f_{L=}$<br>$f_{L=}$<br>R to I<br>$f_{R=}$<br>$f_{R=}$                        |         |            |               |
| 1 dB Conversion Compression<br>$f_{L @}$<br>$f_{L @}$   |         |            |               |
| Input IP3<br>$f_{R1=}$ $f_{R2=}$<br>$f_{L=}$<br><br>$f_{R1=}$ $f_{R2=}$<br>$f_{L=}$<br><br>$f_{R1=}$ $f_{R2=}$<br>$f_{L=}$  |         |            |               |

### Absolute Maximum Ratings

|                       |
|-----------------------|
| Operating Temperature |
| Storage Temperature   |
| Peak Input Power      |
| Peak Input Current    |

### Outline Drawing(s)

|         |        |       |
|---------|--------|-------|
| Package | Figure | Model |
|         |        |       |