

# T-1 3/4 (5mm) BI-COLOR INDICATOR LAMP




# SUN LED

XLUGY59W

Email : sales@us.sunled.com

Web Site : www.sunled.com



- 1 ANODE GREEN
- 2 COMMON CATHODE
- 3 ANODE YELLOW

**Notes:**


1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25(0.01") unless otherwise noted.

Absolute maximum ratings (T <sub>A</sub> =25°C)		UG (GaP)	UY (GaAsP/GaP)	Unit
Reverse voltage	V <sub>R</sub>	5	5	V
Forward current	I <sub>F</sub>	25	30	mA
Forward current (peak) 1/10Duty cycle 0.1ms pulse width	i <sub>FS</sub>	140	140	mA
Power dissipation	P <sub>T</sub>	105	105	mW
Operating temperature	T <sub>A</sub>	-40 ~ +85	-40 ~ +85	°C
Storage temperature	T <sub>stg</sub>	-40 ~ +85	-40 ~ +85	
Lead solder temperature [2mm below package base]	260°C For 5 Seconds			

Operating Characteristics (T <sub>A</sub> =25°C)		UG (GaP)	UY (GaAsP/GaP)	Unit
Forward voltage (typ.) (I <sub>F</sub> =20mA)	V <sub>F</sub>	2.2	2.1	V
Forward voltage (max.) (I <sub>F</sub> =20mA)	V <sub>F</sub>	2.5	2.5	V
Reverse current (V <sub>R</sub> =5V)	I <sub>R</sub>	10	10	uA
Wavelength at peak emission (I <sub>F</sub> =20mA)	λ <sub>peak</sub>	565	590	nm
Wavelength at Dominate emission (I <sub>F</sub> =20mA)	λ <sub>D</sub>	568	588	nm
Spectral Line half-width (I <sub>F</sub> =20mA)	Δλ	30	35	nm
Capacitance (V <sub>F</sub> =0V, f=1MHz)	C	15	20	pF

Part Number	Emitting Color	Emitting Material	Lens-color	Luminous Intensity (I <sub>F</sub> =20mA) mcd		Wavelength nm λ <sub>P</sub>	Viewing Angle 2θ1/2
				min.	typ.		
XLUGY59W	Green	GaP	Water Clear	70	148	565	24°
	Yellow	GaAsP/GaP		20	58	590	

# XLUGY59W



## ◆UG/UY

